



- Variable 0-70% Bypass
- High level of scale reduction
- Mixed blend of ION exchange resin
- Filters bad taste/odour/ chlorine
- Service system available

VH-IEN

Variable Bypass/Scale Reduction Vending Filters

SPECIFICATION

| | VH-IEN 1500 | VH-IEN 3000 | VH-IEN 6000 | VH-IEN 9000 |
|-------------------|--------------------------|-------------|-------------|-------------|
| Flow Rate Ltr/min | 1 | 1 | 1 | 1.67 |
| Pressure Range | 30-100 PSI | | | |
| Max Temperature | 38°C | | | |
| Capacity @10° dH | 1532 | 3006 | 6002 | 9000 |
| Micron Rating | 10 Micron | | | |
| Fittings | 3/8" Pushfit Connections | | | |

DIMENSIONS

| | VH-IEN 1500 | VH-IEN 3000 | VH-IEN 6000 | VH-IEN 9000 |
|-----------|-------------|-------------|-------------|-------------|
| Height mm | 350 | 405 | 405 | 550 |
| Width mm | 110 | 110 | 150 | 150 |
| Depth mm | 110 | 110 | 150 | 150 |

Glastonbury Spring Water Co Ltd

T: 01458 834344

E: sales@glastonburyspringwater.co.uk