

## Storm (Bottom-Load water dispenser)



Our new Bottom-Load water dispenser is the latest model in Crystal Mountain's line of coolers. The Bottom-Load means no more lifting heavy bottles, just open the front door and the bottle slides into the base of the cooler with little effort. The Storm features an easy to remove reservoir system, that takes less than a minute to change. The LED indicator tells you when it needs to be replaced. Servicing has never been easier. With its contemporary design, attractive finish, concealed faucets and easy maintenance, the Storm is sure to dazzle in any environment.

Model: Storm: **Hot & Cold**



LED Night Light, Low bottle Indicator and replace **SmartFlo SF-1** Indicator



Hidden Bottle with front Door



Replaceable Reservoir System - **SmartFlo SF-1 Water Cartridge**



### Specifications:

ITEM		SPECIFICATIONS
Power rating		Single phase
		220-240VAC 50Hz
Standard current		H&C: 2.4~2.7A
Power Consumption	Cold	70W
	Hot	450W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Temp range	7°C ±3°C(44.6°F ±5.4°F)
	Temp control	thermostat (ON 8 °C ±1.5°C, OFF 4 °C ±1.5°C)
	Capacity	1.6L (0.4 gal)
Hot	Heater	Internal heater
	Temp range	76-92°C (168.8-197.6°F)
	Safety device	Bimetal (Manual reset: 95°C OFF)



	Temp control	Bimetal (83°C)(181.4°F)
	Capacity (Internal Heater)	1.1L (0.3 gal)
Refrigerant charge		35g (1.2 oz)
Noise(sound power level)		Pump:55dB(A); Compressor:42dB(A)
Product weight		H&C: 14.5kg (32.0 lb)
Product boxed weight		H&C: 16.2kg (35.7 lb)
Product dimensions		340(W) x 320(D) x 1116(H)mm
		13.4" (W) X 12.6" (D) X 44.0" (H)
Product boxed dimensions		380(W) X 340(D) X 1165(H)mm
		15.0" (W) X 13.4" (D) X 45.9" (H)
Loading quantity		20' Container: 204 Units
		40' Container: 420 Units
Certifications		C-UL-US, CE, CB, EPA

Telephone: 01458 834344 or Email: [sales@glastonburyspringwater.co.uk](mailto:sales@glastonburyspringwater.co.uk)